

LINOVISION

4G LTE MIMO + WiFi 3-in-1 Combo
Antenna
ANT-4GCombo3
Quick Guide (V1.1/2026-6-18)




Quick Guide


Installation

1


Hole size::
0.45"(11.32mm)




2



3



4



Specifications

Model	ANT-4GCombo3	
LTE Antenna	Frequency Range	698-960MHz/1710-2690MHz
	V.S.W.R	<3.0
	Polarization	Linear
	Gain	2.5dBi (Zenith)
	Impedance	50Ω
LTE Antenna AUX	Frequency Range	698-960MHz/1710-2690MHz
	V.S.W.R	<3.0
	Polarization	Linear
	Gain	2.0dBi (Zenith)
	Impedance	50Ω
WIFI Antenna	Frequency Range	2400-2483.5MHz/4900-5825 MHz
	V.S.W.R	<2.0
	Polarization	Linear
	Gain	3.0dBi (Zenith)
	Impedance	50Ω
Mechanical	Cable	RG174
	Connector	SMA or others
	Material	ABS
	Mounting Method	Screw
Environmental	Operating Temperature	-40°C~+85°C
	Relative Humidity	Up to 95%
	Ingress Protection	IP67 (exclude cable outlet)
	Vibration	10 to 55Hz with 1.5mm amplitude 2hours
	Environmentally Friendly	ROHS Compliant